

NOTES:

- ALL ACCESSIBLE PARKING SPACES ARE TO HAVE A HARD, LEVEL SURFACE WITH A MAXIMUM SLOPE OF 1.5% AND A MAXIMUM CROSS
- ALL ACCESSIBLE PARKING SPACES ARE TO BE LOCATED ON THE SHORTEST ACCESSIBLE ROUTE OF TRAVEL FROM AN ACCESSIBLE BUILDING ENTRANCE. WHERE BUILDINGS HAVE MULTIPLE ACCESSIBLE ENTRANCES, THE SPACES MAY BE DISPERSED EQUALLY AROUND THE ENTRANCES.
- WHERE THERE ARE MORE THAN TWO ACCESSIBLE SPACES LOCATED 3. TOGETHER, THIS STANDARD IS TO BE REPEATED.
- LINE PAINTING:
 - ALL LINES ARE TO BE YELLOW IN COLOUR AND 100mm IN WIDTH.
 - THE INTERNATIONAL SYMBOL OF ACCESSIBILITY IS TO BE WHITE IN COLOUR

NO.	REVISIONS	APR'D	DATE
1	REVISED TOWN LOGO	TOI	APRIL 2015
2	REVISED WIDTH DIMENSION	TOI	APRIL 2020
3	CORRECTED TYPO	TOI	MAY 2021



DETAIL FOR ACCESSIBLE PARKING

METRIC ALL DIMENSIONS IN mm UNLESS OTHERWISE NOTED

DRAWN: A&A	APR'D:		
SCALE: N.T.S.	DATE: JUNE 2011		

TOISD 213