



NOTES:

- FOR SINGLE RESIDENTIAL DWELLINGS:
USE 125mm DIAMETER FOR SANITARY SERVICES
USE 150mm DIAMETER FOR STORM SERVICES
- MINIMUM SANITARY SERVICE CONNECTION SIZE FOR SINGLE COMMERCIAL / INDUSTRIAL / INSTITUTIONAL BUILDING TO BE 150mm DIAMETER.
- TEST FITTING SIZE TO BE:
125mm x 100mm FOR SANITARY SERVICES TO SINGLE RESIDENTIAL DWELLING
150mm x 100mm FOR STORM SERVICES TO RESIDENTIAL SUMP PUMP DISCHARGE
- COLOUR OF SANITARY SERVICE PIPE TO BE GREEN.
- COLOUR OF STORM SERVICE PIPE TO BE WHITE OR GREY.
- GENERAL BACKFILL TO BE SELECT NATIVE BACKFILL MATERIAL.
- REFER TO TOWN DESIGN STANDARDS FOR APPROVED MATERIALS.
- MINIMUM DEPTH OF COVER AS PER TOWN DESIGN STANDARDS.
- COMMERCIAL / INDUSTRIAL / INSTITUTIONAL PROPERTIES SHALL HAVE MAINTENANCE HOLE, A MINIMUM OF 0.3m FROM THE PROPERTY LINE IN ACCORDANCE WITH TOISD 608



**TYPICAL SEWER SERVICE
LATERAL CONNECTION DETAIL**

DRAWN:

APR'D:

SCALE: N.T.S.

DATE: JUNE 2011

3.	REVISED NOTES	TOI	SEPT 2025
2.	REVISED DETAIL & NOTES	TOI	MAY 2022
1.	REVISED TOWN LOGO	TOI	APRIL 2015
NO.	REVISIONS	APR'D	DATE

METRIC
ALL DIMENSIONS IN MM
UNLESS OTHERWISE NOTED

**TOISD
605**