



NOTES:

1. FOR LAYOUT, SEE APPROVED SUBDIVISION / SITEPLAN / ENGINEERING / TREE PRESERVATION PLANS
2. TREE PROTECTION BARRIERS MUST BE 1.2m HIGH
3. FILTER FABRIC REQUIRED FOR EROSION CONTROL AS DIRECTED.
4. WHERE SOME EXCAVATE OR FILL HAS TO BE TEMPORARILY LOCATED NEAR A TREE PROTECTION BARRIER, FILTER FABRIC OR PLYWOOD MUST BE USED TO ENSURE NO MATERIAL ENTERS THE PROTECTION ZONE.
5. ALL SUPPORTS AND BRACING SHOULD BE OUTSIDE THE PROTECTION ZONE. ALL SUCH SUPPORTS SHOULD MINIMIZE DAMAGING ROOTS OUTSIDE THE TREE PROTECTION BARRIER.
6. NO CONSTRUCTION ACTIVITY, GRADE CHANGES, SURFACE TREATMENT OR EXCAVATIONS OF ANY KIND ARE PERMITTED WITHIN THE TREE PROTECTION ZONE.

1	ADDED REFERENCE TO TOISD 906	TOI	APRIL 2015
NO.	REVISIONS	APRD	DATE



TREE PROTECTION BARRIER

DRAWN: A&A

APRD:

SCALE: N.T.S.

DATE: JUNE 2011

METRIC
ALL DIMENSIONS IN mm
UNLESS OTHERWISE NOTED

**TOISD
905**